


Adaptor jack/jack  
N jack (female) / BNC jack (female)

AD-N2B25A/H4-H



All dimensions are in mm [inch]  
Tolerances according to DIN ISO 2768-mH

#### Interface

N side according to IEC 61169-16; MIL-C-39012; MIL-STD-348A/304  
BNC side according to IEC 60169-8; MIL-C-39012; MIL-STD-348A/301

#### Electrical Data

Impedance 50 Ω  
Frequency DC to 4 GHz  
VSWR (Return Loss) ≤ 1.20 (≥ 20.83 dB)  
Insertion Loss ≤ 0.05 x √F [GHz] dB

#### Mechanical Data

Coupling mechanisms N (Screw-lock); BNC (Bayonet-lock)  
Weight N/A

#### Environmental Data

Temperature range -65°C to +165°C  
RoHS compliant

#### Material And Plating

Piece Parts (N)	Material	Plating
Centre contact	Phosphor Bronze	Gold plating(Nickel underplated)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	

Piece Parts (BNC)	Material	Plating
Centre contact	Phosphor Bronze	Gold plating(Nickel underplated)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	

#### Packing

Single or 100